

WINTEC

ACS-S60E



Fresh Market



Seafood Market



Green Grocery



Deli



Snack Shop



Supermarket



Convenience Store



Bakery



Solid and reliable metal platform
Fanless design



Optional AI camera
Fast and accurate product identification



Module design
Easy maintenance



High performance printer adapts to high frequency use



Certified by NMI laboratory



Waterproof, insectproof and dustproof design for harsh scenarios



ACS-S60E Specification



CPU

N97: Quad Core 2.0GHz, 3.6GHz(Turbo)
I3-1115G4: Dual Core 3.0GHz, 4.1GHz(Turbo)
I5-1235U: 10 cores 2.5GHz, 4.4GHz(Turbo)

Memory

8GB, up to 32GB

Storage

128GB, up to 512GB

AI camera

2D camera
(200W pixels,
wide dynamic)

Printer

60mm Label printer

Main Display

15.6" LCD, 1366*768
(PCAP)

2nd Display (Optional)

15.6" LCD, 1366*768
(PCAP)
11.6" LCD, 1366*768
(PCAP)

Interfaces

4*USB, 2*RS232(RJ48),
1*RJ45, 1*DK,
1*DC_IN, 1*Audio,
1*HDMI

Scale

Range:6/15kg;
Accuracy:2/5g
Range:15/30kg;
Accuracy:5/10g

Ethernet

10/100/1000M

OS

Win10/11, Linux

Dimension

369*438*533(mm)

Power Adapter

AC input 100~240V, 50-60Hz
DC output 24V/2.5A

Platter Size

362*277 (mm)

Speaker

1*5W

WiFi&BT

802.11 b/g/n + BT4.0

Temperature

Working temperature:
-10~45°C
Storage temperature:
-20~60°C

Humidity

Operating humidity:
20%~90%RH
Storage Humidity:
10%~90%RH

Options

MSR(3 tracks),
RFID card reader,
AI camera

ACS-S60E Specification



CPU

Quad Core 2.0GHz

Memory

4GB

Storage

32GB

AI camera

2D camera
(200W pixels,
wide dynamic)

Printer

60mm Label printer

Main Display

15.6" LCD, 1366*768
(PCAP)

2nd Display(Optional)

15.6" LCD, 1366*768(PCAP)
11.6" LCD, 1366*768(PCAP)

Interfaces

4*USB, 2*RS232(RJ48), 1*RJ45,
1*DK, 1*DC_IN, 1*Audio, 1*OTG,
1*HDMI

Scale

Range:6/15kg;
Accuracy:2/5g
Range:15/30kg;
Accuracy:5/10g

Ethernet

10/100/1000M

OS

Android 11

Dimension

369*438*533(mm)

Power Adapter

AC input 100~240V, 50-60Hz
DC output 24V/2.5A

Platter Size

362*277 (mm)

Speaker

1*5W

WiFi&BT

802.11 b/g/n + BT4.0

Temperature

Working temperature:
-10~45°C
Storage temperature:
-20~60°C

Humidity

Operating humidity:
20%~90%RH
Storage Humidity:
10%~90%RH

Options

MSR(3 tracks),
RFID card reader,
AI camera